

Pannelli Operatori HMI

AXIOM DISPLAY

NARDIELETRONICA



AXIOM - T43

| Modello | AXIOM T4.3 | AXIOM T7 | AXIOM PLUS | AXIOM PLUS-P | AXIOM T102 | AXIOM-B | AXIOM-G |
|---------------------------|----------------|----------------|------------------|------------------|-------------------|---------------------|------------------|
| Dimensione Display | 4,3" (95x54mm) | 7" (152x91mm) | 7" (152x91mm) | 7" (152x91mm) | 10,2" (220x132mm) | - | 5,1" (114x63mm) |
| Risoluzione Display | 480x272 pixel | 800x480 pixel | 800x480 pixel | 800x480 pixel | 800x480 pixel | 4 righe x 20 carat. | 240x128 pixel |
| Numero colori | 65536 | 65536 | 262144 | 262144 | 65536 | 2 | 2 |
| Tipo retroilluminazione | LED | LED | LED | LED | LED | LED | LED |
| Touchscreen | SI | SI | SI | SI | SI | - | - |
| Tasti programmabili | - | - | - | 12 | - | 24 | 24 |
| Led programmabili | - | - | - | - | - | 13 | 6 |
| Linea seriale Rs232 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Linea seriale RS422-485 | 1 | 1 | - | - | 1 | 1 | 1 |
| Protocollo MOD-BUS | SI | SI | SI | SI | SI | SI | SI |
| Linea CAN-OPEN | - | - | 1 | 1 | - | 1 | 1 |
| Profilo DS-401 | - | - | SI | SI | - | SI | SI |
| Numero porte USB | 1 | 1 | 2 | 2 | 1 | (1) Optional | (1) Optional |
| Tipo porta USB | Programmazione | Programmazione | 1 Host- 1 Device | 1 Host- 1 Device | Programmazione | Host-Device set. | Host-Device set. |
| Porta Ethernet | - | Optional | 10-100 Mbit | 10-100 Mbit | Optional | - | - |
| Memoria Flash | 32Mbyte | 32Mbyte | 32Mbyte | 32Mbyte | 32Mbyte | 1Mbyte | 1Mbyte |
| Memoria Ram | 64Mbyte ddr | 64Mbyte ddr | 64Mbyte ddr | 64Mbyte ddr | 64Mbyte ddr | 512Kbyte sram | 512Kbyte sram |
| Memoria esterna | - | SD card | USB | USB | - | - | - |
| Tipo CPU | 32 bit 400Mhz | 32 bit 400Mhz | 32 bit 600Mhz | 32 bit 600Mhz | 32 bit 400Mhz | 32 bit 16Mhz | 32 bit 16Mhz |
| Sistema operativo | Proprietario | Proprietario | Windows CE 6.0 | Windows CE 6.0 | Proprietario | Proprietario | Proprietario |
| Fungo emergenza | - | - | - | SI | - | - | - |
| Tasto "uomo morto" | - | - | - | SI | - | - | - |
| Tensione alimentazione | 24Vdc +/- 15% | 24Vdc +/- 15% | 24Vdc +/- 15% | 24Vdc +/- 15% | 24Vdc +/- 15% | 24Vdc +/- 15% | 24Vdc +/- 15% |
| Grado protezione frontale | IP65 | IP65 | IP65 | IP20 | IP65 | IP65 | IP65 |
| Dimensioni esterne lxbxp | 138x86x37 mm | 212x146x36 mm | 226x155x40 mm | 226x155x40 mm | 272x200x48 mm | 210x140x60 mm | 210x190x60 mm |
| Dima di foratura | 131x79 mm | 193x139 mm | 120x120 mm | Palmare | 260x179 mm | 190x135 mm | 190x170 mm |



AXIOM - T7



AXIOM - B



AXIOM - B



AXIOM - PLUS PALMARE



AXIOM-PLUS



AXIOM - T102

